

# Identification result of material property and analysis model: Hardness (65), Damping (Large)

ADINA

Prony series

$$G(t) = G_{\infty} + \sum_{n=1}^N G_n \exp(-\beta_n t)$$

$$K(t) = K_{\infty} + \sum_{n=1}^N K_n \exp(-\gamma_n t)$$

Parameter

$G_n$ (MPa)		$\beta_n$	
$G_{\infty}$	0.93407		
$G_1$	3.2570	$\beta_1$	500
$G_2$	0.29622	$\beta_2$	10
$G_3$	0.70441	$\beta_3$	0.5


  

$K_n$ (MPa)		$\gamma_n$	
$K_{\infty}$	3.61E5	$\gamma_1$	
$K_1$		$\gamma_2$	
$K_2$		$\gamma_3$	
$K_3$		$\gamma_4$	

Amplitude:  $A = 1 \text{ mm} (A^* = 0.25)$

Frequency:  $f = 0.2 \sim 15 \text{ Hz}$


Displacement:  $\delta = A^* \sin 2\pi f$




Analysis model

# Analytical result of shear test (Constant amplitude): Hardness (65), Damping (Large)


ADINA




Input File: case0\_2.in



Input File: case1\_0.in




Input File: case0\_5.in




Input File: case2\_0.in

# Analytical result of shear test (Constant amplitude): Hardness (65), Damping (Large)


ADINA



Input File: case5\_0.in



Input File: case15\_0.in



Input File: case10\_0.in